PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of	Docket No: Q82799
Ludovic NOIRIE	
Appln. No.: 10/509,429	Group Art Unit: 2874
Confirmation No.: 3427	Examiner: Michael J. Stahl
Filed: September 24, 2004	

For: BROADCAST SIGNAL CROSS-CONNECT UNIT, IN PARTICULAR FOR OPTICAL SIGNALS

AMENDMENT UNDER 37 C.F.R. § 1.111

MAIL STOP AMENDMENT
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

In response to the Office Action dated April 21, 2006, please amend the above-identified application as follows on the accompanying pages.

TABLE OF CONTENTS

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (Presently amended) A space cross-connect unit (Z) with N input ports (E_i) and P output ports (S_i), comprising:

a broadcast stage comprising at most N signal dividers (A_i) each having one input and C outputs where C is an integer factor of P less than P, each input being connected to one of said N input ports (E_i) so that each of said N dividers (A_i) divides a signal received at one of said N input ports (E_i) into C signals at said C outputs, and

a space switching stage comprising at most C space switching modules (B_i, B'_i),

~~which~~said space cross-connect unit is characterized in that:

the [[C]] space switching modules (B_i, B'_i) are non-blocking and non-broadcasting, and

each of said [[C]]space switching modules (B_i, B'_i) has N inputs and P/C outputs, said N inputs are connected to N outputs of said broadcast stage, each of said N outputs comes from a different divider (A_i), and each of said P/C outputs of said [[C]]space switching modules (B_i, B'_i) is connected to a respective one of said P output ports (S_i), wherein said space cross-connect unit is configured for packet switching and circuit switching, and wherein said space cross-connect unit is adapted to provide broadcasting of input signals independently of spectral considerations.

2. (Original) A cross-connect unit (Z) according to claim 1, comprising exactly N dividers (A_i) and C modules (B_i, B'_i).

3. (Presently Amended) A cross-connect unit (Z) according to claim 1, characterized in that each of said [[C]]space switching modules (B_i, B'_i) comprises means for connecting each of its N inputs to one of its P/C outputs.

4. (Presently Amended) A cross-connect unit (Z) according to claim 1, characterized in that each of said [[C]]space switching switching modules (B_i, B'_i) is a non-blocking switching matrix (B_i) with N inputs and P/C outputs.

5. (Presently Amended) A cross-connect unit (Z) according to claim 1, characterized in that each of said [[C]]space switching switching modules (B'_i) comprises:

K non-blocking switching matrices (F_i) with N/K inputs and P/C outputs, where K is an integer factor of N; and

P/C non-blocking switching matrices (G_i) with K inputs and one output, each of said K inputs being connected to a respective output of each of said K switches (Fi).

6. (Presently Amended) A cross-connect unit (Z) according to claim 1, characterized in that at least one of said [[C]]space switching switching modules (B'_i) comprises:

K non-blocking switching matrices (F_i) with N/K inputs and P/C outputs, where K is an integer factor of N; and

P/C non-blocking switching matrices (G_i) with K inputs and one output, each of said K inputs being connected to a respective output of each of said K switches (F_i).

7. (Presently Amended) A cross-connect unit (Z) according to claim [[1]]5, characterized in that said P/C switching matrices (G_i) are semiconductor optical amplifier (SOA) switches.

8. (Original) A cross-connect unit (Z) according to claim 1, characterized in that said number N of input ports is equal to said number P of output ports.

9. (Original) A cross-connect unit (Z) according to claim 5, characterized in that K is equal to C.

10. (Original) A cross-connect unit (Z) according to claim 1, characterized in that said switching stage uses a technology based on $LiNbO_3$.

11. (Presently Amended) A cross-connect unit (Z) according to claim 1, characterized in that each of said P/C outputs of said [[C]]space switching modules (B_i, B'_i) is followed by an amplifier (D_S).

12. (Presently Amended) A cross-connect unit according to claim 1, characterized in that ~~each of said N inputs of said N dividers~~the input of each divider is preceded by an amplifier (D_E).

13. (Presently Amended) A cross-connect unit (Z) according to claim 1, characterized in that each of said space switching modules (B_i, B'_i) comprises:

a first stage comprising polarization-maintaining space switching matrices (M_1, …, M_K); and

a second stage comprising polarization-maintaining semiconductor optical amplifiers ~~(MQWSOPA$_1$, …, MQWSOA$_k$)~~(MQWSOA$_1$, …, MQWSOA$_k$).

14. (Previously Presented) A signal transmission system comprising a cross-connect unit (Z) according to claim 1 and characterized in that said system comprises:

at least one multiplexer for multiplexing M signals having M different wavelengths $(\lambda_i)_{1\leq i\leq M}$, where M is an integer less than or equal to N;

at least one erbium-doped fiber amplifier (EDFA) for amplifying the multiplexed signal; and

at least one demultiplexer for demultiplexing the multiplexed signal to yield M demultiplexed signal that are input to M input ports of said cross-connect unit.

15. (New) A cross-connect unit (Z) according to claim 6, characterized in that said P/C switching matrices (G_i) are semiconductor optical amplifier (SOA) switches.

16. (New), The cross-connect unit of claim 1, wherein said number of dividers is less than N.